

SAFE HOME CITY OF CHARLOTTE NEIGHBORHOOD & BUSINESS SERVICES

Invitation to Bid

HNS 21-23

SAFEHOME CHARLOTTE

NOTE: Contractors are not authorized to visit the property before or after the bid walk, without being accompanied by the City's Rehabilitation Specialist.

Documents included in Package:

- 1) Instruction to Bidders
- 2) Specs by Location/Trade (Scope of Work)
- 3) Subcontractor Certifications (if applicable)
- 4) Floor Plan / Site Drawing (if applicable)

Bid Walk & Bid Opening:

responsive and disqualified.

Project Address:

4737 Kenmant	Dr.
Bid Walk: 2 \ 4 \ 2020	e , 9:00 AM
Bid Opening:\2\2\2020	e 2:00 PM
Client Name: Altesa Wright	Contact Number: 704-584-8380
Project Manager: C. Hitsman	Contact Number: 704 622 1685
Bid Walk and Bidding Instructions: All bid walks are mandatory.	
If you are going to be late the policy is the following: Contact me BEFORE the start time if you are going to be minutes late, we will proceed without you and you will	
The day of a bid walk the best way to reach me is at $_$	(cell # _704 622 1685).

The Bids will be opened at 600 East Trade St. immediately following the above due date and time.

Bids must be received by the date, time and place specified. All others will be considered non



SAFE HOME

CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Carrier Ask audadament	
Company Acknowledgement:	
provisions of the housing improve through the City of Charlotte Ne inspected the site in all particulars, time stated and in strict accordance and all labor and materials, and to advised respective contractual, for All labor, materials, services and	d equipment necessary for the completion of the Work shown
on the Drawings and in the Spe	
	Dollars (\$)
Written total	
Specs Dated: 8 \3\2 0 Numbe	r of Pages:
Addenda # 1 Dated:	Number of Pages:
Addenda # 2 Dated:	Number of Pages:
Project Schedule: Minimum Start	Date -
Completion Deadline:	, ,)
Please Print and Sign:	
Company Name/Firm:	
Authorized Representative Name:	
Signature:	Date:



SAFE HOME CITY OF CHARLOTTE NEIGHBORHOOD & BUSINESS SERVICES

Requirements For Bidders

The City awards rehabilitation bids to the lowest responsive and responsible bidder. A responsible bidder for the safe home program is one who:

- 1) Is a licensed general contractor in the State of North Carolina;
- 2) Has an Renovate, Repair & Paint Certification (http://www2.epa.gov/lead/renovation-repair-and-painting-program);
- 3) Is not listed on a local, state or federal debarment list;
- 4) Carries an appropriate amounts of insurance;
- 5) Can provide references verifying the contractor has completed work of a similar scope in a good workmanship like manner or successfully completed prior work for the Safe Home program. Referenced work must have been completed in one year or less from date of this invitation to bid.

A responsive bidder must:

- 1) Submit all requested documentation on time;
- 2) Meet the above requirements for responsibility at the time of bid submittal;
- 3) Have the capacity to meet the required schedule for the project.
- 4) Existing rehab projects contracted by the contractor must be on schedule.

The City reserves the right to waive any minor informalities or irregularities, which do not go to the heart of the bid submittal or prejudice other offers, or to reject, for good and compelling reasons, any or all bid submittals.

Rehabilitation Specialist
City of Charlotte
Neighborhood and Business Services
600 E. Trade St.
Charlotte, NC 28202
PH: (704)
Fax: (704)



SAFE HOME

CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Instructions to Bidders

Explanations to Bidders

Any explanation desired by a Contractor regarding the meaning or interpretation of the advertisement for bids, drawings, specifications, etc., must be requested in writing to the Rehabilitation Specialist with sufficient time allowed for a reply to each Contractor before the submission of their bids. Any interpretation made will be in the form of an addendum to the invitation for bids, drawings, specifications, etc., and will be furnished to all prospective Contractors. The Contractor must acknowledge any revision to the bid documents in the space provided on the bid form and it must be submitted with their bid package.

Preparation of Bids

Bids shall be submitted on the forms furnished, or copies thereof, and must be manually signed. If erasures or other changes appear on the forms, the person signing the bids must initial each erasure or change

- The Contractor's Bid Proposal must be properly executed and submitted on the form provided. Bids by Contractors must be received by the Rehabilitation Specialist at the time and place specified on the "Invitation to Bid"
- No bid will be considered unless all individual work items on the Bid Form including any addendums are priced. The sum of all work items must equal to the Total Bid Amount.
- Unless called for, alternate bids will not be considered
- Modification of bids already submitted will be considered if received at the office designated in the invitation for bids by the time set for opening of bids

Submittal of Bids

- Sealed bids will be submitted to the Safe Home Program Office as directed in the invitation to bid prior to or at the appointed bid opening time
- Bid will be time stamped on the date of delivery
- Each bid must be submitted in a sealed envelope bearing on the outside the name of the Contractor, the name of the project for which the bid is submitted, and the date and time of the bid opening
- All bids submitted must be typed or written in ink and signed by the Contractor's designated representative

G:\SELECTIVE REHAB TEAM\forms\bid forms and documents\Invitation to bid WARREN



SAFE HOME

CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

- Failure to include all forms may result in rejection of a bid
- Required Bid Package Forms:
 - o Scope of Work
 - o Addenda Acknowledgement
 - o Itemized Work Sheet
 - Subcontractor Certifications (if applicable)

NEIGHBORHOOD & BUSINESS SERVICES

http://housing.charlottenc.gov | 600 E. Trade Street | Charlotte, NC

Prepared By:
City of Charlotte Housing & Neighborhood Services
600 E. Trade Street
Charlotte, NC 28202
(704) 336-7600

Λ	do	ro	SS	٠

4737 Kenmont Dr

Charlotte, NC 28269

Owner:

Altesa Wright

Owner Phone:

Cell: (704) 584-8380

Program(s):

Healthy Homes

SHFY2020

Structure Type: Square Feet:

1000

Single Unit

Year Built:

1000

rear built.

1966 91000

Property Value: Tax Parcel:

04505129

Census Tract:

Property Zone:

Council District 4

Repairs

Description

Floor

Room

Exterior

All Contractor's Project Requirements

The contractor is responsible for project requirements, including but limited to:

COVID - 19 Processes

Obtaining all permits required. Said permits shall include all items in this scope of work.

Provide temporary toilet facilities from job start until the completion of work.

Provide AS MANY roll-off dumpsters as needed without damaging the site. Collect construction debris using dust control methods. Remove dumpster and repair any evidence of the dumpsters use. Contractor may haul debris away daily using dump trailers.

Bid Cost:		Х	=	
_	Base	Quantit	У	Total Cost

Tear Off & Reroof Shingles

Remove and dispose of existing roofing, inspect and repair roof deck (include 96 sq.ft. of decking replacement in bid) and install new 30 year architectural shingles. Include ice and water shield at all roof edges, felt paper, shingle over ridge vent, boots, flashing and all necessary accessories.

Bid C	Cost:		x	=	
magnetic control of the control of t	,	Base	Quantity		ıl Cost
Demo and Rebuild Bathroom - Complete	nt Eligiphia No. 1911	entere alla virgi di	ezer see an america and a subject of	a service e e e averagosidos es	To and device of the original and major
Completely demo the existing bathroom. Remove all plumbing and electoverings to the framing. Repair or replace all framing as necessary to the Building Code. Replace / paint any affected adjoining room drywall	ectrical fi o meet th	xtures, doors ne requiremen	and trim, and nts of the Cons	ceiling, wall, and struction Specific	d floor cations and
Rebuild the bathroom complete with all the following features: *floor, wall, and ceiling insulation at locations required by the Construct *ceiling mounted fan vented through the roof *switched light fixture centered over the vanity *GFCI outlet per Code *4" fiberglass shower pan & 4x4 tile, bull-nosed edging, 5 ft tall, include					
*drywall and finish walls and ceiling					•
*25 yr vinyl resiliant flooring *prehung six panel door and hardware					
*baseboard and shoe mold at standard locations					
*1.6 gpf commode 17"					
*24" vanity with cultured marble top and single handle faucet *3 piece bath hardware set (towel bar, paper holder, and towel ring)					
*mirror centered over the vanity					
*floor supply register					
*walls and ceiling painted semi-gloss per Construction Specifications.					
* replace window with Code compliant window.					
All materials and construction methods shall meet the requirements of	the relev	ant Construc	tion Specificati	ons and the NC	Codes.
Bid Co	ost:		, <u> </u>	Mercel Secret	
a personalement to the productive of the contraction of the contractive of the following state of the productive of the contractive of the contrac	900	Base	Quantity		Cost
Exterminate Termites		1000	- Mary Company and Down Co. 46	Company to the company of the Compan	ar ar Mitmeenico
Exterminate for termites. Drill and patch foundation and pavement whe year guarantee with an optional yearly renewable warranty for the home	re neces: eowner.	sary, Extermi	nator must be	licensed and pro	ovide a 1
Bid Co	ost:	Х		=	
		Base	Quantity	Total	Cost
NACONI TROP SERVICIO DE COMO DE COMO DE SERVICIO DE COMO DE CONTRADO. LE COMPANSA DE COMO DE COMO DE COMO DE C	za i Afrika zapa i sorri. — Jirak eki	th common with the change the figures.	um mena ter tanaan i retar ni musuk sito ng	C ESSENTE BAMANS (1998 F. PERMANENCE CORE	ship or burn porces, necessaries

Insulate Floor R-19

Install R-19 Kraft faced batt fiberglass insulation to floor where missing. Vapor barrier must face heated space. Use strong wire, "tiger teeth" or mesh to hold insulation in place.

	Bid Cost:		X	·
		Base	Quantity	Total Cost
Attic Insulation Increase to R-38	er teat to the teater of the teater of the	A space of the same of the same and the	10 July 10 Jul	
Increase attic insulation to R-38, contractor to attach verific code.	cation to rafter at at	tic access, eas	sily seen. Include	ventilation baffles to
	Bid Cost:	;	х	=
		Base	Quantity	
Vapor Barrier	tion to a section of a section of the section of th	and the control of th	en antas de la compania de la compa	Annual Marian Control of the Control
Lay 6 mil poly vapor barrier on ground in crawl space and	6" up foundation w	alls. Overlap s	eams by 2' and se	ecure with duct tape,
	Pid Contr	,	v	=
	Did Cost	Base	Quantity	.= Total Cost
Activity of the second control of the second	subside it in the concentration of American relief	ren autro. No orientamento per	ann saisteirine an III Alea (e.g. Lleas ear feilige	normalista de traj lingua de l'estado estado estado en el
Dispose of window units and any security bars. Field measured windows including half screens, insulate rough opening. In			•	ad nrime and naint
Dispose of window units and any security bars. Field meast windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fragioists and sill. Any windows replaced in a bathroom must be supported by the control of the control	nstall new extension as needed. Repair a aming (to include kin have tempered glas	n jambs, casing all areas disturi ng studs, jack ss.	g and sill as needd bed by removal a studs etc.) sub-flo	nd installation. This or, floor joists, band
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra	nstall new extension as needed. Repair a aming (to include kin have tempered glas	n jambs, casing all areas disturi ng studs, jack ss.	g and sill as needd bed by removal a studs etc.) sub-flo	nd installation. This or, floor joists, band
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost:	n jambs, casing all areas disturing studs, jack as. Base	g and sill as needd bed by removal a studs etc.) sub-flo X	nd installation. This or, floor joists, band = Total Cost
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be prehung Metal Doors (3)	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost:	n jambs, casing all areas disturing studs, jack as. Base	g and sill as needd bed by removal a studs etc.) sub-flo X	nd installation. This or, floor joists, band = Total Cost
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost: hergy Star rated prestall wide peep sigl	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing	g and sill as needd bed by removal a studs etc.) sub-flow Quantity door. Insulate ca and shoe moldin	nd installation. This or, floor joists, band Total Cost vity. Install mortised g will match existing.
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be a better that the present of the property of the	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost: hergy Star rated prestall wide peep sigl	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing neader, door from the casing the case are also as a case	g and sill as needd bed by removal a studs etc.) sub-flow Quantity door. Insulate ca and shoe moldin	nd installation. This or, floor joists, band Total Cost vity. Install mortised g will match existing.
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be prehung Metal Doors (3) Front, Rear & Utility Doors Remove existing door, frame and threshold. Install new Erdead bolt and lever handled door hardware keyed alike. In Apply primer and topcoat. This installation to include repair	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost: Dergy Star rated prestall wide peep siglering any damaged in	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing neader, door from the casing the case are also as a case	g and sill as needd bed by removal a studs etc.) sub-flow Quantity Quantity door. Insulate ca and shoe moldin aming, to include	nd installation. This or, floor joists, band Total Cost vity. Install mortised g will match existing.
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be prehung Metal Doors (3) Front, Rear & Utility Doors Remove existing door, frame and threshold. Install new Erdead bolt and lever handled door hardware keyed alike. In Apply primer and topcoat. This installation to include repair	nstall new extension as needed. Repair a aming (to include kin have tempered glas Bid Cost: Dergy Star rated prestall wide peep siglering any damaged in	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing neader, door fr	g and sill as needs bed by removal a studs etc.) sub-flo X Quantity door. Insulate ca and shoe moldin raming, to include	nd installation. This for, floor joists, band Total Cost vity. Install mortised g will match existing. wall framing, sub-floor,
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be a better that the property of th	astall new extension as needed. Repair a saming (to include kinhave tempered glasses) Bid Cost:	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing a neader, door from a sase	g and sill as needs bed by removal a studs etc.) sub-flo X Quantity door. Insulate ca and shoe moldin raming, to include X Quantity	nd installation. This for, floor joists, band Total Cost vity. Install mortised g will match existing. wall framing, sub-floor, Total Cost h a back flow preventer
windows including half screens. Insulate rough opening. In Exterior trim to be wrapped in PVC coated aluminum coil a installation is to include repairing any damaged header, fra joists and sill. Any windows replaced in a bathroom must be provided in the	astall new extension as needed. Repair a saming (to include kinhave tempered glasses) Bid Cost:	a jambs, casing all areas disturing studs, jack as. Base -hung exterior at. New casing a neader, door from a sase	g and sill as needs bed by removal a studs etc.) sub-flo X Quantity door. Insulate ca and shoe moldin raming, to include X Quantity	nd installation. This for, floor joists, band Total Cost vity. Install mortised g will match existing. wall framing, sub-floor, Total Cost h a back flow preventer

Combination CO / Smoke Detector Hard Wired

Install a hard wired combination carbon monoxide and smoke detector with battery back up.

	Bid Cost:	>	(## ## ## ## ## ## ## ## ## ## ## ## ##
		Base	Quantity	Total Cost
Smoke Detector Hard Wired	guar y austroprocessamentares un relativo de 1900 de 200 Euro			
Install UL approved, interconnected, ceiling mounted sn battery backups in bedrooms and outside of sleeping ar	noke and heat detecto reas.	rs permanently	y wired into a rec	eptacle boxes with
	Bid Cost:		K	=
		Base	Quantity	Total Cost
LED Screw Base Bulb Installation	arde en programme programme en el commente de la co	V - V - WW - 1. 15 mil 24 V - 11	5 1714 July 177 Male Day 1704 July 1	
Replace all existing screw base (A-Type) lamps through Contractor to field verify quantity needed.	nout the house with LE	D screw base	d omni directiona	al (A-Type) lamps.
	Bid Cost:		x	=
		Base	Quantity	Total Cost
Electrical Scope - Outlets	, i	e e e e e e e e e e e e e e e e e e e		
Replace, to Code any loose wall outlets in dwelling				
•				
	Bid Cost:		х	=
	Bid Cost: _	Base	XQuantity	=Total Cost
Double Bowl Sink Complete	Bid Cost:			= Total Cost
	steel, self rimming kito anty, P-trap, supply lir	Base	Quantity ding a single ha	ndle metal body faucet,
Double Bowl Sink Complete / Install a 18 gauge 33" x 22" x 8" double bowl, stainless rated at 2.0 GPM or less, with a 15 year drip- free warr	steel, self rimming kito ranty, P-trap, supply lir ngs.	Base shen sink inclu ses, full port ba	Quantity ding a single ha	ndle metal body faucet,
Double Bowl Sink Complete / Install a 18 gauge 33" x 22" x 8" double bowl, stainless rated at 2.0 GPM or less, with a 15 year drip- free warr	steel, self rimming kito anty, P-trap, supply lir	Base shen sink inclu ses, full port ba	Quantity ding a single har all type shut-off v	ndle metal body faucet,
Double Bowl Sink Complete / Install a 18 gauge 33" x 22" x 8" double bowl, stainless rated at 2.0 GPM or less, with a 15 year drip- free warr	steel, self rimming kito ranty, P-trap, supply lir ngs.	Base then sink inclu les, full port ba	Quantity ding a single had all type shut-off v	ndle metal body faucet, alves & escutcheon plate: =
Double Bowl Sink Complete Install a 18 gauge 33" x 22" x 8" double bowl, stainless rated at 2.0 GPM or less, with a 15 year drip- free warr on all supply & drain lines. No copper compression fitting	steel, self rimming kitoranty, P-trap, supply lirngs. Bid Cost:	Base chen sink inclu ies, full port ba Base end-caps and	Quantity ding a single had all type shut-off v Quantity cutout for sink.	ndle metal body faucet, alves & escutcheon plate = Total Cost
Double Bowl Sink Complete Install a 18 gauge 33" x 22" x 8" double bowl, stainless rated at 2.0 GPM or less, with a 15 year drip- free warr on all supply & drain lines. No copper compression fitting Counter Tops Replace Screw to base cabinet a square edged plastic laminate	steel, self rimming kitoranty, P-trap, supply lirngs. Bid Cost:	Base shen sink incluies, full port ba Base end-caps and in-stock color	Quantity ding a single had all type shut-off v Quantity cutout for sink.	ndle metal body faucet, alves & escutcheon plates = Total Cost

Cabinets Base

Replace base cabinets. Cabinets to be constructed of solid maple and plywood. No particle board allowed. See contractor's manual guidelines & specifications for full requirements.

	Bid Cost:	Base	X = Quantity	Total Cost
Cabinets Wall	and the second section of the section of t	your trouve for the towns	e enderste nichte der den eine Stein verweitung in Angelein des Anstellen	ak ra ma suusa na ausang mauk magamaay magamaa masa maa magama sak mina masa mak kind
Replace wall cabinets. Cabinets are to be constructed of solio manual guidelines & specifications for full requirements. * Place two (2) cabinets (sized) center over stove * Place two (2) cabinets (sized) over dryer	d maple and ply	wood. No pa	rticle board allowed. S	See contractor's
	Bid Cost:		x	
		Base	Quantity	
Range Hood Exterior Vented	a great in special and kind of decidence of the special and th	s existing a later of the second contraction of the second		SPECIAL CONTRACT OF SERVICE SPECIAL CONTRACTOR OF SERVICE SPECIAL
Install an exterior ducted enameled range hood with integral c cabinet with screws. Include metal vent and roof or wall cap/d	ontrols and ligh lamper assemb	t capable of 1 ly, using #14	00 cfm at 70 sones. A copper Romex. Own	Attach hood to er's choice of color.
	Bid Cost: _		_X=_	
	ANTEN OF PROCESS OF TRANSPORT OF LINES		Quantity	Total Cost
Prep & Paint Ceiling - Kitchen				
Remove or cover hardware and accessories not to be painted fungus, dirt, and dust from surfaces. Fill holes and cracks. Prir with Owner's choice of low VOC acrylic flat latex in all habitable Replace or uncover hardware, fixtures and accessories. Any r	me all new mate le rooms and lo	erials and spo w VOC acryli	ot prime existing with a c semi-gloss latex in k	crylic latex. Top coat
	Bid Cost:		_X=_	
		Base	Quantity	Total Cost
Ceiling Fan with Light - Kichen	garan kanagaran garan dayar da	noncourse being the C.S. being gives	gerale agent groups a spekin an an earlier to be	
Install a 52" 3 speed flush mounted ceiling fan with a minimum ceiling fan mounting box. New fan is to be Energy Star rated.	n two bulb UL a	pproved, LEC) light fixture with shad	de and lamps. Include
	Bid Cost:		x =	
	Dia 0031	Base	Quantity	Total Cost
				i Otai Oost

Floor System Repair - Kitchen Health Homes

Remove all fixtures not built in. Dispose of damaged/unsafe components of floor assembly. Work may include installation of 2"x 8" joists hung 16" on center, plywood or tongue and groove subfloor, wall studs & plates. Include replacing all deteriorated band joists and insulating floor to code.

	Bid Cost:		χ :	=
	,	Base	Quantity	Total Cost
Resilient Flooring - Kitchen	general in programment in the programment and describe about	and the state of t	A Mark Committee of the	inger (11 million) versione (1500 ender 1600) visus
Install 25 year warrantied resilient floor covering per manufa and be waterproof. Include transitions and painted or stain				
	Bid Cost:		_X:	=
		Base	Quantity	Total Cost
Laundry Washer Connection Box - Kitchen	tanda (n. 18. jungan) (n. 19. jungan) - manudadan adapat (n. 19. jungan)	and the second second second	<u>augus egi i un reista a un arte i dado i i teòrica ce arte i a</u> r	Anna ann an Air an Anna an Air an Aire ann an
machine. Repair wall studs, plates and girder below if needed. Repla insulation. Existing Drain line is inoperable.	ce any wood pane	iling removed	l for piping. Seal all	air gaps, include
	Bid Cost:		_X:	
		Base	Quantity	Total Cost
Replumb Waste Lines & Vents				
Remove all drain, waste and wet vent lines to code legal du laundry area from the roof vent pipe/pipes thru the foundati			o service one 3-pie	
outs required, installed to code. Repair any wall or ceiling t new clean-out. Snake line from new clean-out to City connection.			out outside of hous	e and any interior clean
new clean-out.		install syste	out outside of hous m. Replace to exte	e and any interior clean
new clean-out. Snake line from new clean-out to City connection.	ear out required to Bid Cost:	o install syste	out outside of hous m. Replace to exte	e and any interior clean
new clean-out.	ear out required to Bid Cost:	o install syste	out outside of hous m. Replace to exte	e and any interior clean rior of foundation wall to =
new clean-out. Snake line from new clean-out to City connection.	ear out required to	o install syste	out outside of hous m. Replace to exte	e and any interior clean rior of foundation wall to =
new clean-out. Snake line from new clean-out to City connection. Asbestos Abatement Scope	ear out required to	Base	out outside of hous m. Replace to exte	e and any interior clean rior of foundation wall to =

Prep & Paint Exterior Surfaces

Prep and paint all exterior painted surfaces. Properly dispose all loose materials. Secure or replace all loose, broken, rotted or deteriorated materials. Caulk and fill all cracks, voids, holes, etc. prior to applying 25-year or better Low VOC paint. Owners choice of color. All work to be done in a neat & professional manner. Use care to protect all surfaces not intended for paint coverage.

	Bid Cost:		(=	
	*	Base	Quantity	Total Cost
REMOVE ATTIC RODENTS				
Trap / Remove Attic Rodents. Screening to be secured over interior side of Gable Vents All extermination shall be performed by a licensed contractor.				
	Bid Cost:		x:	=
		Base	Quantity	Total Cost
Folding Attic Stairs Replace utility folding stairway, after doubling framing at ceiling assembly	. Install casing	to match trim	in room. (2) coal	s paint on trim and do
Replace utility folding stairway, after doubling framing at ceiling				s paint on trim and doc
Replace utility folding stairway, after doubling framing at ceiling			x	=
Replace utility folding stairway, after doubling framing at ceiling assembly				s paint on trim and doc
Replace utility folding stairway, after doubling framing at ceiling			x	=
Replace utility folding stairway, after doubling framing at ceiling assembly			x	= Total Cost

ASBESTOS	AB.	ATEME	N
& INSTRUCTIONS	TO	BIDDE	RS

SCOPE OF WORK

N. Carolina Certified Asbestos Contractor Required for Abatement

Address
Complete the following scope of works

4737 KENMONT AVE 11/9/0220
Work to be performed by a Licensed N. Carolina Asbestos Abatement Contractor

Complete the following scope of work: Number Cost Per unit COST Feature Method Item # Approximately 500 sq ft of White Joint Compound on the Wallboard joints, seams Permit Required. N. Carolina and connection points on the first floor of the Certified Asbestos Contractor to remove and house. Areas of concern: Bathroom, kitchen, properly dispose of the asbestos containing joint windows, doors, attic stairs, CO2 & Smoke compound material prior to renovation or demolition activites that may impact the material. detectors, laundry washer connect box Contractor to use Roy Consulting Group to provide Asbestos Clearance testing. City of Charlotte will pay for the testing. Clearance required

total

Contractors may submit an occupant protection plan on the form provided.

- 1 Contact Roy Consulting Group if an additional form is needed. Phone 704-968 4111 Complete all interior work in a unit in a single day.
- 2 Allow for replacement of 50 board feet of rotted wood.
- 3 Unless otherwise noted any window or door removal and replacement
- 4 includes frame and trim on both sides.
 - In lieu of complete removal, window frames may be enclosed with vinyl on
- 5 exterior in accordance with all project manual requirements
- 6 Contact Jim Roy to conduct inspections prior to repainting or other putback and after vinyl siding installation.

Windows being placed in a bathroom need to be tempered glass.

Total	Bid
-------	-----

10

Acknowledgement of Addenda (if any):

Addendum#			
			D
The undersigned conti	ractor agrees to perfo	rm the scope of work for the indicated	

fee in accordance with applicable regulations and the project manual. The undersigned also certifies that the work will be completed within 60 days of award.

Signature of authorized contractor representative

Contractor Submitting Bid:

START DATE

COMPLETION DATE

ROY CONSULTING

GROUP CORPORATION

Providing integrated environmental and geotechnical solutions

4737 Kenmont Drive

Charlotte, NC 28269

THE CLASSIC CONTRACT WAS A WAS

SIDE D

SIDE B

Legend

+ = Window

X = Soil Sample Location

SIDEA

OT TO SCAL

NC Lead-Based Paint Program for Renovation, Repair, and Painting Guidance Document - Recordkeeping Checklist

Project Date(s):	Project/Job Number:
Target Housing □	Child-Occupied Facility (COF) □ Year Built:
Complete Address of Physical Address of Pagerintian of Pager	cupant: of Owner: Renovation (If Different): vation or Scope of work (attach a copy if available): tion, describe the nature of the emergency and document the provisions of the NC-RRP Rules
NC Certified Lead F Firm Certificate)	ed Lead Renovation Firm: (Attach Copy of Renovation Firm Number: (Example: RRP-124) (Attach Copy of Renovator Assigned to Project: (Attach Copy of Renovator Number: (Example: 172469)
NC Certified Lead	Renovator provided lead safe training to workers on (mark all that apply):
Posting Warn	ng Signs (Occupant Protection)
Setting Up & I	Maintaining Containment(s) / Interior / Exterior
Using Person	al Protection Equipment Prohibited & Restricted Work Practices
Isolate Work / Openings, Co	Area, Remove or Cover Objects, Close Windows/Doors, Close & Cover Ductover Floors or Ground (Avoid Spreading of Lead Dust to Adjacent Areas)
Post-Renovat	ion Cleaning (Interior/Exterior) Waste Handling
Other	
Name(s) of Lead Sa	afe Trained Worker(s), if used:,
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Pre-Renovation E	ducation - (select method used):
Renovation Form" wi	n acknowledgment of receipt of pamphlet - Attached "Renovate Right pamphlet - Pre- th signature of owner/occupant and renovator or renovator's self-certification (for tenant- ly) prior to starting work <i>OR</i> ,
Documented co	ertificate of mailing at least 7 days prior to starting renovation but no earlier than 60 days <i>OR</i> ,
with general nature of review or obtain a co	pied Facility (COF) or common area renovations, posted pamphlet & information signs f work, location of work, start and completion dates and how parents & guardians can py of the Renovate Right pamphlet, project records and reports at no cost. Firm prepared ment describing steps to inform all parents & guardians of intended renovation.

NC Lead-Based Paint Program for Renovation, Repair, and Painting Guidance Document - Recordkeeping Checklist (Page 2 of 4)

Lead-Based Paint (LBP) Testing or Inspection Results (select method used):

Painted or coated surfaces are assumed to contain Lead-Based Paint (LBP) unless tested. I. Check if Assumed LBP N/A 🗆 II: Was a LBP inspection or written determination done by a NC Certified Lead Inspector/Risk Assessor? (If yes, attach a copy of the inspection report or written determination) Yes □ N/A \square N/A III. Did a NC certified renovator test for lead using an EPA recognized test kit? Yes □ If yes, you must provide LBP testing results in writing to the person who contracted for the renovation **prior** to starting work. Results provided: Yes

N/A

Date provided Record testing results below. Use supplemental sheets to record additional testing results if needed. **Renovator Testing:** EPA - Recognized Lead Test Kit Documentation Name of Kit Used: Serial/Lot Number: _____Expiration Date: ____ (if applicable) List the Room Location(s), All Component(s) and the Results of each test. LBP: Yes or No Room Component Date Sample No. **Paint Chip Sampling Documentation** List the Room Location(s), All Component(s) and the Results of the testing. LBP is 0.50% (5000 PPM) or Greater. Usually minimum 1 square inch (in²) sample needed, check with NLLAP laboratory. LBP: Yes or Area (in²) Component Dimension Date Sample Room (inches) No No.

(Find NLLAP labs at: http://www2.epa.gov/lead/national-lead-laboratory-accreditation-program-list)

Page 2

Note: Attach copy of analysis results from NLLAP laboratory

NC Lead-Based Paint Program for Renovation, Repair, and Painting Guidance Document - Recordkeeping Checklist (Page 3 of 4)

Project Date	: Project/Job Number:
Physical Add	dress of Renovation:
(Mark All Th	nat Apply)
General Wo	rk Practices:
V	Varning signs posted at entrance to work area
V	Vork area contained to prevent spread of dust and debris
V	Vork site properly cleaned after renovation
F	Personal Protective Equipment (used as needed - disposable suits/booties, etc.)
V	Vashing station provided (face and hand washing)
<i>A</i>	At the conclusion of each work day, waste contained on-site is stored to prevent access nd release of dust or debris. Waste contained while being transported off-site.
Interior wor	·k:
	All objects in the work area removed or covered with plastic with edges/seams sealed
	Ducts (e.g., HVAC, etc.) in the work area closed, covered with plastic and sealed
	Windows in the work area closed
	Doors in the work area closed and sealed
	Doors used to enter the work area are covered to allow passage of workers, but prevent spread of dust
	Floors in the work area covered with taped-down plastic, minimum 6 feet from renovated surface
	Work area surfaces and objects cleaned using HEPA vacuum and/or wet cloths or mops
Exterior Wo	ork:
(Closed windows and doors in and within 20 feet of the work area
	Doors used to enter the work area are covered to allow passage of workers, but prevent spread of dust
(Ground covered by plastic sheeting extending 10 feet or more from work area – plastic sheeting anchored to building and edges weighed down
p	Vertical containment erected if the renovation will affect surfaces within 10 feet of the property line or extra precautions were taken to prevent migration of dust and debris to adjacent property
	All chips and debris picked up, protective sheeting misted, folded dirty side inward, and taped for removal

NC Lead-Based Paint Program for Renovation, Repair, and Painting Guidance Document - Recordkeeping Checklist (Page 4 of 4)

Not Applicable (N/A) or leave blank Cleaning Not Applicable (N/A) or leave blank Cleaning Verification First Wipe *Second *Dry Wipe Verification First Wipe *Second *Dry Wipe Verification First Wipe *Second *Wipe *Second *Wipe Verification First Wipe *Second *Wipe *Second *Wip	iducted	exterior work	I/A: No	<u> </u>	Passed: _	on: Date l	sual Inspecti	Exterior: Vis
Note: In order to pass an interior visual inspection there can't be any visible debris, paint chips or resion any surfaces, including all objects and surfaces in the work area and within two feet of the work area For interior work use the appropriate number of wet/dry wipe(s) for each window sill, uncarpeted floor and countertops surface inside the work area. List each of the areas or rooms (ex. bedroom, living room hallway, etc.) where cleaning verification was performed in the following table(s). If dust clearance was performed in lieu of cleaning verification, attach a copy of the results. (Example)	paint chips or residue	any visible deb	n there can't be a	ual inspectio				
on any surfaces, including all objects and surfaces in the work area and within two feet of the work area For interior work use the appropriate number of wet/dry wipe(s) for <u>each</u> window sill, uncarpeted floor and countertop surface inside the work area. List each of the areas or rooms (ex. bedroom, living roor hallway, etc.) where cleaning verification was performed in the following table(s). If dust clearance was performed in lieu of cleaning verification, attach a copy of the results. (Example)	k conducted	_ No interior	N/A:		⊃assed: _	on: Date F	sual Inspecti	Interior: Vis
Not Applicable (N/A) or leave blank Cleaning Not Applicable (N/A) or leave blank Verification Kitchen First Wipe * Second *Dry Wipe Verification First Wipe * Second *Dry Wipe Verification First Wipe * Second *Wipe * Second * Wipe *	et of the work area. uncarpeted floor edroom, living room,	and within two each window as or rooms (ex wing table(s).	in the work area t/dry wipe(s) for g each of the area ormed in the follow	und surfaces umber of we rk area. Lis on was perfo	all objects a propriate n side the wo ig verificati	including a use the ap surface ins ere cleanin	ny surfaces, interior work countertop vay, etc.) wh	on a For i and hallv
Verification Veri	rk column Pass (P), Fail (F) or Applicable (N/A) or leave blan						Area/Room	(Example)
Window Sills **Number & Size Uncarpeted Floors **(48 ft²) F2-P Number of Countertops ***Other Surfaces Date Completed Example: S1 represents 1st sill wiped, S2 represents 2nd sill wiped, F1 represents 1st sill wiped, S2 represents 2nd sill wiped, F1 represents 1st surface wipe on floor and surfaces **Second wet wipe (if needed) conducted only after re-cleaning the failed work area(s). Dry wipe (if needed) user only after second wet wipe failure and after re-cleaning the failed work area. Allow surface to dry or wait 1 hour (whichever is longer) before performing dry wipe. **For surface areas greater than 40 ft², divide the area roughly into equal sections (each area less than 40 ft²) are a separate wipe for each area. *** Other surfaces the renovator may choose to perform CV on, but are not required by regulatory work practic Note: Note: The NC certified lead renovation firm is required to submit a copy of information, documenting complian to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 da after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow	vvipe i				* Second		Kitchen	Cleaning
Number & Size Uncarpeted Floors **(48 ft²) F2-P **(24 ft²) Number of Countertops *Other Surfaces Date Completed **Second wet wipe (if needed) conducted only after re-cleaning the failed work area(s). Dry wipe (if needed) use only after second wet wipe failure and after re-cleaning the failed work area. Allow surface to dry or wait 1 hour (whichever is longer) before performing dry wipe. ***For surface areas greater than 40 ft², divide the area roughly into equal sections (each area less than 40 ft²) at use a separate wipe for each area. ***Other surfaces the renovator may choose to perform CV on, but are not required by regulatory work practic Note: The NC certified lead renovation firm is required to submit a copy of information, documenting complian to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 da after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow			1	N/A	52-Pass	ľ	>2	
*** Other Surfaces Pantry shelving Pantry shelving shelving Pantry shelving shelving Pantry shelving sh			Size Uncarpeted		N/A	F1-P (24 ft²) F2-P		Size Uncarpeted
Surfaces Shelving P		Ī		C2-P	C2-F	i .	>2 <u> </u>	
Example: S1 represents 1 st sill wiped, S2 represents 2 nd sill wiped, F1 represents 1 st surface wipe on floor and standard wipe (if needed) conducted only after re-cleaning the failed work area(s). Dry wipe (if needed) use only after second wet wipe failure and after re-cleaning the failed work area. Allow surface to dry or wait 1 hour (whichever is longer) before performing dry wipe. **For surface areas greater than 40 ft², divide the area roughly into equal sections (each area less than 40 ft²) at use a separate wipe for each area. *** Other surfaces the renovator may choose to perform CV on, but are not required by regulatory work practic Note: The NC certified lead renovation firm is required to submit a copy of information, documenting complian to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 da after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow			1			Р	,	
*Second wet wipe (if needed) conducted only after re-cleaning the failed work area(s). Dry wipe (if needed) used only after second wet wipe failure and after re-cleaning the failed work area. Allow surface to dry or wait 1 hour (whichever is longer) before performing dry wipe. **For surface areas greater than 40 ft², divide the area roughly into equal sections (each area less than 40 ft²) at use a separate wipe for each area. *** Other surfaces the renovator may choose to perform CV on, but are not required by regulatory work practic Note: The NC certified lead renovation firm is required to submit a copy of information, documenting complian to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 day after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow			1					Date Completed
to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 da after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow	pe (if needed) used dry or wait 1 hour	rk area(s). Dry Allow surface	ng the failed wo failed work area.	ter re-clean leaning the e.	ted only at d after re-c ng dry wip	ed) conduc failure and e performi r than 40 fi	vipe (if needo and wet wipe onger) befor areas greate	Second wet wonly after seco whichever is l
to the building owner, or if different, the owner or occupant, upon delivery of final invoice or within 30 da after completing the renovation, whichever is earlier. Date when a copy of records were provided to ow	atory work practice.	required by re	/ on, but are not	perform C\	/ choose to	ovator may	aces the ren	*** Other surfa
	ice or within 30 days	elivery of final i copy of record	ccupant, upon de er. Date when a	e owner or c ever is earli	lifferent, the tion, which	vner, or if d the renova	ne building over completing	to th
I certify that the information provided on this checklist is true and complete:		mplete:	list is true and co	n this check	provided o	nformation	tify that the i	I cer

Disclaimer: The information reflected on this recordkeeping checklist is provided as a resource tool only and the checklist itself is not required to be used. It is subject to change without notice. The information contained in this or future versions are not intended to be all inclusive and should not be interpreted as such. All applicable renovation activities must comply with the North Carolina General Statutes §130A-453.22-453.31 and the rules adopted to implement the Lead-Based Paint Hazard Management Program for Renovation, Repair and Painting (LHMP-RRP) 10A NCAC 41C .0900. For questions regarding the LHMP-RRP, contact the Health Hazards Control Unit at (919) 707-5950 or visit our website at: http://epi.publichealth.nc.gov/lead/lhmp.html.